

East Dune Trading (Pty) Ltd T/A



51 Gerhardus Street, Strijdom Park, South Africa
 P.O.Box 912 North Riding 2160 South Africa
 Tel: 011 466 8250
 Email: shop@waterhouse.co.za
 Reg.No. 2008/010619/07 VAT No: 4200247635

PRODUCT MANUAL



Pump Design	5 chamber Daiphragm
Port size	3/4"(19mm) Quick attach
Connector	1pc 3/4" Male Thread , 1pc 1/2" hose barb , 1pc 1/2" hose barb filter
Voltage	12V, 24V
Check value	EPDM or VITON
Liquid temp	140F(60C) maximum
Seld-priming	8 feet (2M) suction Lift



Model number	Volt	Max Flow LPM(GPM)	Max Pressure Psi(Bar)	Amps(A)	Packing Size(mm)	N.W/G.W
FL-55	12v dc	20(5.2)	55(3.8)	16.0	240*135*138mm	3.2/3.5kgs
FL-200	12v dc	10(2.6)	200(13.8)	15.0	210*125*105mm	3.2/3.5kgs
FL-200B	24v dc	10(2.6)	200(13.8)	7.5	210*125*105mm	3.2/3.5kgs

Director: S Soal

East Dune Trading (Pty) Ltd T/A



51 Gerhardus Street, Strijdom Park, South Africa
P.O.Box 912 North Riding 2160 South Africa
Tel: 011 466 8250
Email: shop@waterhouse.co.za
Reg.No. 2008/010619/07 VAT No: 4200247635

caravan,RV,marine, garden,camping,boat, outdoor,agriculture irrigation



- Adjustable pressure switch from 50psi-200psi for OEM needed
- Built-in thermal protector
- Quick attach connections, fittings easy to connect with any outlet.
- Rubber feet for noise reduction from vibration



CAUTION:

- Intermittent use only – 30 minutes ON and 20 minutes OFF. It needs to cool down to ambient temperature.
- Frequent start/stop cycling should be avoided
- A possible reason for causing failure – Leaks on the system will cause the pump to cycle, this leads to the failure of the Pressure Switch. Examples: poor connection, Gardena fittings, Ball valve or taps not shutting off properly.
- Low voltage forces the pump to run continuously and not reach the cut-off pressure of 2.4 bar, resulting in the motor burning out.

XDP series designed with a 5 chamber high volume diaphragm.

Pump pressure 200PSi (14 bar) with self-priming ability.

XDP High-Pressure agricultural pumps use Viton seals widely for liquid PH value vary between 4-11PH.

Note: Because of the high pressure, clamps should be used to secure tubing.

Rubber feet fitted for noise and vibration reduction.

Small, Portable & lightweight.

Mount in a vertical position and use a flexible high-pressure hose.

Shaft made of Stainless steel for heavy-duty pressure.

Beware to avoid kinking pipes.

NOT for pumping flammable liquids.