



Performance Curves







i Prez - **22N**



Technical Details

Output Frequency : 20 to 50 Hz / 20 to 60 Hz

Pressure Setting Range : up to 9 Bar 24V, 4-20mA

Pressure Transmitter : up to 40°C up to 70°C up

Ambient Temperature : to 68m up to 11m3/h

Liquid Temperature : Head Range : Flow Range :

Power Range	0.75kW / 1.1kW	1.5kW	2.2kW
Input Voltage	1Ph - 220V	1Ph - 220V	1Ph - 220V
Frequency	50Hz / 60Hz	50Hz / 60Hz	50Hz / 60Hz
VFD Output	3Ph - 220V	3Ph - 220V	3Ph - 220V

In view of continuous developments the information / performance / descriptions / specifications / Illustrations are subject to change without notice.

C.RI PUMPS (PVT) LIMITED

(International Division)

7/46-1, Keeranatham Road, Saravanampatty, Coimbatore - 641 035. India.
Phone: +91-422-7117310, 7117312. Fax: +91-422-7117300,
e-mail: cri@crifluidsystems.com website: www.crifluidsystems.com







HIGH EFFICIENC ENERGY SAVING




Touch with new advance Variable Speed technology

i Prez

Booster System (with VSD)

i Prez Series are basically domestic pressure

boosting system with built-in Variable speed for constant pressure in pipe line. The pressure transducer in this system monitors pressure at any time. i Prez also protects the system from dry run, over loading, unbalanced voltages, short circuit etc. The system comprises of Horizontal Multistage Pump, VSD, 5 Way connector with built in NRV, pressure tank, Pressure gauge & pressure transducer.



- Plug & play type
- Soft start increases smooth functioning and better life to the pump set
- Protects the pumpest from High voltage, low voltage, dry run, over load, underload etc.,





